

# GENERAL INFORMATION

Unit: mm (in)

## ELECTRIC STARTER

ITEM	STANDARD	SERVICE LIMIT
Starter motor brush length	12.5 (0.49)	6.5 (0.26)

## LIGHTS/METERS/SWITCHES

ITEM	SPECIFICATIONS	
Bulbs	Headlight (High/low beam)	12V-60/55W
	Brake/tail light	12V-32/3CP × 2
	Front turn signal/running light	12V-21/5W × 2
	Rear turn signal light	12V-21W × 2
	License light	12V-4CP
	Instrument light	12V-3.4W
	Turn signal indicator	12V-1.7W
	High beam indicator	12V-1.7W
	Neutral indicator	12V-1.7W
Fuse	Main fuse	30A
	Sub fuse	10A × 3, 15A × 1
Fuel pump flow capacity (min./minute) ('97 - '98 models)		800 cm <sup>3</sup> (27.1 US oz, 28.2 Imp oz)
Fan motor switch	Start to close (ON)	98 - 102°C (208 - 216°F)
	Start to open (OFF)	93 - 97°C (199 - 207°F)
Thermosensor resistance ('97 - '00)	50 °C/122 °F	130 - 180 Ω
	80 °C/176 °F	45 - 60 Ω
	120 °C/248 °F	10 - 20 Ω
Thermo switch (After '00)	Start to close (ON)	112 - 118°C (259 - 270°F)
	Start to open (OFF)	Below 108°C (252°F)